


Items for a complete flooring installation with Altro flooring products.



C7 Cap strip

C7Cap

Pliable "J" shaped vinyl finishing cap used with flash coved sheet vinyl flooring. Available in Black, Gray and White.



Stainless steel cap strip

SSCAP67

Stainless steel "j" shape finishing cap used with flash cove sheet vinyl flooring.
Finish: 304 #4 stainless steel finish
Gauge: 20



C8 Cap tile strip

C8Cap

Rigid "h" shaped vinyl transition cap w/8mm shelf to be used between flash coved sheet flooring and wall tiles and/or wall cladding.



20mm Cove stick

CF 20R

Depicts colors


Used to create flash coving with resilient sheet flooring.



Stainless steel corner guard

3" and 5"

Protects external corners in high traffic areas.



C4 Cap tile strip

C4Cap

Pliable "h" shaped vinyl transition cap w/4mm shelf to be used between flash coved sheet flooring and Altro wall panels.



38mm Cove stick

CF 38R


Used to create flash coving with resilient sheet flooring.



C11 Captile strip

C11Cap

Pliable vinyl finishing cap used at the top of quarry tile base or similar when flash coving over existing tile.



Gulley angle

GA 25/35

Vinyl "L" shaped accessory to be heat welded to sheet vinyl and used with raised floor sinks that are higher than the finished floor level.

Available in Black, Storm (Dark Gray), Fog (Light Gray), Russet (Quarry Red) and Tundra.



20mm Joint cover strip


JCS 75/20

Cover strip used when there is potential of control joints moving and showing through the finished floor.



Visedge DS

Aluminum over the top reducer threshold to finish a raw edge of flooring where it needs to transition down to zero.



20mm Gulley edge with reducer

GE 25 RE

Vinyl "T" shaped accessory to be heat welded to sheet vinyl and used with floor sinks, square or rectangular trench drains that are flush with the finished floor level. Available in Black, Storm (Dark Gray), Fog (Light Gray), Russet (Quarry Red) and Tundra.



32mm Joint cover strip


JCS 75/32

Cover strip used when there is potential of control joints moving and showing through the finished floor.



Visedge VR

Aluminum alloy retainer with pvc insert to receive heat welded sheet vinyl that can abut a raised floor sink or quarry tile and patched down to zero.



35mm Gulley edge with reducer

GE 35 RE

Vinyl "T" shaped accessory to be heat welded to sheet vinyl and used with floor sinks, square or rectangular trench drains that are flush with the finished floor level. Available in Black, Storm (Dark Gray), Fog (Light Gray), Russet (Quarry Red) and Tundra.



Shower transition trim

ASF WETTRIM/* color code


Wheel chair accessible shower berm that prevents water egress from wet areas. Available in Cream(01), Light Gray(03), Medium Gray(04) and Light Brown (02).



Stainless steel heat deflector plate

4'3

Protects vinyl flooring from high radiant heat. Ships with protective film covering.



WSBU 200 vinyl shim

WSBU200

Vinyl shim use for transitioning smoothly between floors and walls or dissimilar flooring thickness when the transition is to be heat welded.



EcoFix 20E adhesive

ECOFIX20E

Environmentally friendly, hard set, acrylic adhesive used for vinyl sheet flooring.



AltroFix 31 adhesive

ALTROFIX31

Fast-acting two-part polyurethane adhesive used for installing safety sheet vinyl in small, wet environments.



EcoFix 65 Spray adhesive

ECOFIX65

Non-toxic, water-based adhesive used for tile and/or plank flooring.



EcoFix 25E adhesive

ECOFIX25E

Environmentally friendly, pressure sensitive, acrylic adhesive used for tile and/or plank flooring.



AltroFix SD70 acrylic adhesive

ALTROFIXSD70

One-part acrylic adhesive used for installing Altro Walkway 20SD in static sensitive areas.



Altro QuickFix 3042 epoxy caulking

QUICKFIX3042

Fast-reacting, two-part self-mix epoxy caulking adhesive used for gulley edge/angle installation and small repairs.



AltroFix 30 adhesive

ALTROFIX30

Two-part polyurethane adhesive used for installing safety sheet vinyl in high traffic and/ or wet areas.



EcoFix 35 Spray adhesive

ECOFIX35

Non-toxic, water-based adhesive used for resilient sheet vinyl flooring in dry environments.



AltroMastic 100

A1M/* add color code.

Caulking compound used for sealing joints where obstructions prevent the use of a heat welding gun.



W165 Tape adhesion promoter W165

Ensures tape adheres properly to substrate.



Weldrod

WR* add color code.

PVC welding rod for use with Altro sheet vinyl flooring.



Adhesive-free tape

For adhering adhesive-free sheet vinyl in place.




Contact tape

1" CFS Capfix

4" and 6" CFS Covefix

Adheres cove stick and flashed coved flooring in place.




Altro Everlay underlayment

For installing sheet vinyl over old or new surfaces with subfloor problems.



Altro Acoustic underlay 1101

For reducing the passage and transmission of sound.



FlashCove

Prefabricated, coved base with a bonded aluminum reinforcing backer.



Altro Drain strainer cover

For ease in creating a modified drain with pre-existing assemblies.