

Acczent Excellence 80

HETEROGENEOUS VINYL

Specification data

2018

The selected flooring similar to Acczent Excellence 80 belongs to the compact vinyl floors category under ISO standard 10582, available in 2m wide sheet with a Type I binder content.

The product formulation does not contain phthalate-based plasticizer. It is built on a calendered backing layer made of recycled vinyl flooring material. It contains over 30% recycled material.

The **wear layer of 0.80 mm** is reinforced with a UV photo-crosslinked polyurethane including particles of alumina TopClean XP™ treatment, which permanently suppresses any wax and regenerating polish spray maintenance operations. It has a **static indentation resistance ≤ 0.03 mm.**

It offers a dimensional stability $\leq 0,10\%$ according to EN ISO 23999 standard. Its gloss rate is $\leq 5\%$ and it can be installed **with multicolour welding rods to ensure seamless finish.**

Its emission rate of volatile organic compounds in air is very low, measured after 28 days according to EN standard 16516. Close to zero emission (quantification limit), **TVOC, TSVOC and formaldehyde emissions are below $10 \mu\text{g}/\text{m}^3$.**

It is free of formaldehyde and is **100% REACH compliant.**

It is 100% recyclable and installation off-cuts can be collected and recycled in new products through the Tarkett ReStart® programme..

Acczent Excellence comes with a **10 Year Warranty.**

More excellent reasons to choose Tarkett Excellence

- ✓ 100% Phthalate Free
- ✓ No formaldehyde
- ✓ 100% recyclable
- ✓ Test reports and certificates available upon request
- ✓ Optimal indoor air quality
- ✓ TVOC $\leq 10 \mu\text{g}/\text{m}^3$ after 28 days
- ✓ FloorScore® certified
- ✓ ISO 14001 certified production site
- ✓ REACH Compliant and CE Marking